

# **BLACKFRIAR PAINTS LTD.** **TECHNICAL DATA SHEET**

Revision Date:  
16/03/10

## **BF0520002 Blackfriar Blackboard Paint.**

<b><u>Product Information</u></b>	<b><u>Technical Spec</u></b>	<b><u>Recommended Spreading Rate</u></b>
<p><b><u>Description</u></b></p> <p>A matt black paint specifically formulated for blackboards.</p> <p><b><u>Usage/purpose</u></b></p> <p>Specifically formulated for painting new or old Blackboards. Ideal for use in pubs, restaurants, play areas etc.</p> <p><b><u>Characteristics</u></b></p> <p>A matt finish paint that gives clarity of chalking, resists ghosting and is easily cleaned.</p> <p><b><u>Finish</u></b></p> <p>Matt Finish</p> <p><b><u>Colour(s)</u></b></p> <p>Black.</p> <p><b><u>Packaging</u></b></p> <p>125ml, 250ml, 500ml, 1litre, 2.5litre.</p> <p><b><u>Disclaimer;</u></b> The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. It is our recommendation that a trial area is first coated to ensure the product is satisfactory to individual requirements.</p>	<p><b><u>Composition</u></b></p> <p>Based on a high quality blend of alkyd resins coupled with carefully selected pigments and extenders to give good chalking clarity and minimal ghosting.</p> <p><b><u>VOC</u></b></p> <p><b>EU limit value for this product (cat A/d):</b> 300 g/l (2010). This product contains max 300 g/l VOC</p> <p><b><u>Performance</u></b></p> <p>Primarily for interior use. May be used externally but will require regular maintenance.</p> <p><b><u>Surface Preparation</u></b></p> <p>Ensure the substrate to be painted is sound and free from any surface contaminant likely to give adhesion problems (e.g. wax, grease etc). Where necessary prime new and bare areas with appropriate Blackfriar Primer</p> <p><b><u>Application Method</u></b></p> <p>Brush, Roller, Spray Ensure products are <u>thoroughly</u> stirred with a broad stirrer. Two full coats are recommended for best results</p> <p><b>For Technical Enquiries Material Safety Data Sheets. Contact Sales on 0191 4106611</b></p>	<p>Approximately 13m<sup>2</sup>/ltr</p> <p><b><u>Drying Time</u></b></p> <p>Hard Dry in 10-16 hours Recoat after 16 hours under normal conditions (20°C 50% RH).</p> <p><b><u>Cleaning</u></b></p> <p>Clean application equipment or spills with white spirit or Blackfriar Brush Cleaner</p> <p><b><u>Limitations</u></b></p> <p><b>Not suitable for use on roller boards or with liquid chalks.</b> Ensure Paint is fully dry prior to use. Some initial ghosting may occur if so clean with a damp rag.</p> <p><b><u>Environmental Info.</u></b></p> <p>Flammable</p> <p>Paint Product UN No. 1263.</p> <p><b>Tor Coatings Ltd. Portobello Industrial Est, Birtley Chester-le Street County Durham DH3 2RE</b></p>