

PRODUCT ADVICE

METAL PRIMER & UNDERCOAT



All Farrow & Ball paints are eco friendly and comply with the latest environmental legislation regarding the VOC (volatile organic compounds) content of paints.

Availability: In 750ml tins in four colours White & Light Tones, Mid Tones, Red & Warm Tones & Dark Tones. Available direct from Farrow & Ball, our Showrooms and selected stockists internationally.

Usage: A primer designed to prevent rust. For both internal and external application.

Preparation: Surfaces must be clean and free from oil, grease, dirt, rust and flaking paint. New and previously painted metal surfaces should be thoroughly degreased. Remove any weak paint and rust back to bare metal.

Painting: **Do not paint in temperatures below 10°C or excessive heat above 30°C.**
Stir thoroughly before use. Apply two coats by brush.

Clean up: Clean brushes and rollers with warm soapy water.

Cleaning: N/A

Formulation: Based on a copolymer emulsion.

Storage: This product is water based and must be protected from frost and extreme temperatures. Use within 6 months of purchase. We accept no responsibility for the deterioration of contents or packaging after this date.

Disposal: Though water based, please do not dispose of into watercourse. Waste materials must be disposed of in accordance with the Environmental Protection Act 1990 and relevant regulations made there under. For further information contact the environment office at your local council.

Health & Safety: Ensure good ventilation during application and drying. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. After contact with skin wash immediately with plenty of soap and water or a proprietary skin cleanser. Keep out of reach of children.

Safety Data Sheets are available for professional users on request.

Environment:	Actual VOC content g/l	1.0g/l
	VOC content w/w:	0.08%
	Classification:	Minimal
	2010 max. permitted limit grams per litre	30g/l
	CATEGORY	g

Coverage	Drying Time	Recoat Time	Sheen Level
Up to 9 m ² per 750 ml	1-2 hours surface dry.	4 hours depending on conditions	N/A

Issue 3 January 2012

Disclaimer: The information given in these specification sheets and technical advice - whether verbal, in writing or by way of trials - is for guidance and is given in good faith but without warranty, since skill of application and site conditions are beyond our control. For further information please contact our Customer Services Department. We can accept no liability for the performance of the products arising out of such use, beyond the value of the goods delivered by us. This does not affect your statutory rights.

PAS_UK