

## PRODUCT ADVICE

### ESTATE® EGGSHELL



All Farrow & Ball paints are eco friendly and comply with the latest environmental legislation regarding the VOC (volatile organic compounds) content of paints.

**Availability:** In 750ml, 2.5 litre and 5 litre tins in all Farrow & Ball colours. Available direct from Farrow & Ball, our Showrooms and selected stockists internationally.

**Usage:** An extremely robust and durable eggshell finish. Ideal for all interior woodwork and metal including radiators. It provides a tough, washable and easily maintained surface.

**Preparation:** All surfaces must be sound, clean, dry and free from dirt, grease and other contamination. **Flaking or peeling may occur if painting over weak paint layers.**

Fill any cracks, holes and open joints with an appropriate flexible filler. Surface filling will require more maintenance. Neutralise when caustic strippers have been used.

Surface filling will require more maintenance. Neutralise when caustic strippers have been used.

**Unsound surfaces** – may not successfully accept further paint layers; if in doubt seek professional advice.

**Interior bare wood surfaces** – where required use Farrow & Ball Wood Knot & Resin Blocking Primer to patch prime knotty or resinous woods. Apply a diluted first coat of Farrow & Ball Interior Wood Primer & Undercoat (20% water) followed by one full coat. Proceed with two coats of Farrow & Ball Estate® Eggshell.

**Previously painted interior wood surfaces** – sand back areas of paint that have peeled or blistered, to achieve a good 'key'. Apply one full coat of Farrow & Ball Interior Wood Primer & Undercoat. Proceed with two coats of Farrow & Ball Estate® Eggshell.

**Interior ferrous metal surfaces** – new and previously painted metal surfaces should be thoroughly degreased. Remove any weak paint and rust back to bare metal. Apply two coats of Farrow & Ball Metal Primer & Undercoat. Proceed with two coats of Farrow & Ball Estate® Eggshell.

**Interior galvanised surfaces** – treat with Etch Primer or Mordant Solution taking care to follow manufacturer's instructions and health and safety advice. Clean with a detergent wash when dry. Proceed with two coats of Farrow & Ball Estate® Eggshell.

**Painting:** Do not paint in temperatures below 10°C or excessive heat above 30°C.

**Please check for colour accuracy prior to use as we will not be liable for decorating costs caused as a result of an incorrect colour being applied. When more than one tin of the same colour is to be used ensure that batch numbers are identical or intermix before use.** Stir thoroughly before use.

Load brush well and apply two coats. May be applied by a gloss roller for larger flat areas. For a perfect finish, lightly sand between coats.

**Airless Spraying** – Good results can be achieved by the set up of 18 thou 65° angle tip using a pressure of between 2400 – 2700 psi – see separate spraying sheet for more details.

**Disclaimer:** The information given in these specification sheets and technical advice – whether verbal, in writing or by way of trials – is for guidance and is given in good faith but without warranty, since skill of application and site conditions are beyond our control. For further information please contact our Customer Services Department. We can accept no liability for the performance of the products arising out of such use, beyond the value of the goods delivered by us. This does not affect your statutory rights.

PAS\_UK

## PRODUCT ADVICE

### ESTATE<sup>®</sup> EGGSHELL



**Clean up:** Clean brushes and rollers with warm soapy water.

**Cleaning:** Washable and wipeable.

**Formulation:** A water based paint made using a traditional alkyd resin.

**Storage:** This product is water based and must be protected from frost and extreme temperatures. Use within 6 months of purchase. We accept no responsibility for the deterioration of contents or packaging after this date.

**Disposal:** Though water based, please do not dispose of into watercourse. Waste materials must be disposed of in accordance with the Environmental Protection Act 1990 and relevant regulations made there under.

**Health & Safety:** For further information contact the Environment Office at your local council. Ensure good ventilation during application and drying. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. After contact with skin wash immediately with plenty of soap and water or a proprietary skin cleanser. Keep out of reach of children.

**Safety Data Sheets are available for professional users on request.**

**Environment** Actual VOC content g/l 4.9 g/l

VOC content w/w: 0.37%

**Classification:** Low

2010 max. permitted limit grams per litre 130 g/l

**CATEGORY** d

Coverage	Drying Time	Recoat Time	Sheen Level
Up to 60 m <sup>2</sup> per 5 litres.	Touch dry 1 hour. Dark colours may take longer to dry.	Minimum 4 hours depending on conditions. Ensure the surface is completely hard before closing newly painted windows and doors.	20%

Issue 4 - January 2012

**Disclaimer:** The information given in these specification sheets and technical advice - whether verbal, in writing or by way of trials - is for guidance and is given in good faith but without warranty, since skill of application and site conditions are beyond our control. For further information please contact our Customer Services Department. We can accept no liability for the performance of the products arising out of such use, beyond the value of the goods delivered by us. This does not affect your statutory rights.

PAS\_UK