

## PRODUCT DATA SHEET

07/2019

Product Name	Single Pack Floor Paint	
Our Reference	6400 Line	
Description	A single pack floor paint based on a urethane-modified alkyd. For light industrial and domestic use. For interior use only. Not suitable for areas of heavy industrial use, car showrooms or garage floors that are in prolonged contact with wet vehicle tyres.	
Colours	Red (04D45), Light Grey (00A05), Grey (10A07), Green (14C 39), White, Yellow	
Gloss Level	Semi-gloss	
Theoretical Spreading Rate	Up to 12 sqm per litre at 30 microns dry film thickness (d.f.t.).	
Drying Time 20°C	Touch Dry	2-4 hours
	Dry to Handle	12-16 hours
Recoating	Minimum interval before recoating 12 hours. No limitation on maximum interval before recoating. A number of factors, such as temperature, air movement, and dry film thickness can substantially alter the through dry/over coating time. We recommend that before recoating a large area, you should do a small test patch	
Application	Brush or Roller	On bare concrete thin first coat up to 20% with BT6 thinner
Surface Preparation	New concrete must be completely dry before painting. All floors must be free of dirt, grease or any other contamination. New power-floated floors should be either acid washed or mechanically prepared to obtain a "key". Existing paint should be checked for compatibility, and then abraded. Please contact our technical department for more information.	
Packaging	5 litres	
Thinner	BT6	
VOC (supplied)	500-550 grams per litre	
Flashpoint	31 °C	
Shelf Life	12 months from date of manufacture in sealed containers. Store in a cool, dry place with temperatures between 5-30 °C and in accordance with the Highly Flammable Liquids and Liquefied Petroleum Gases Regulations 1972	